CALIFORNIA BEARING RATIO (CBR) ANALYSIS

1. PROJECT		2. DATE
3. SOIL CLASSIFICATION	4. LOCATION OF SOIL	5. GROUP NUMBER

DATA SUMMARY

MOLD NUMBER	BLOWS PER LAYER	MOISTURE CONTENT, *W* *(percent)*	DRY DENSITY	CORRECTED CBR *(percent)*	SWELL *(percent)*

CBR - MOISTURE

CORRECTED CBR IN PERCENT



MOLDING WATER CONTENT (w)
(IN PERCENT) OF DRY WEIGHT

DENSITY - MOISTURE

DRY DENSITY IN POUNDS PER CU FT



MOLDING WATER CONTENT (w)
(IN PERCENT) OF DRY WEIGHT

6. TECHNICIAN *(Signature)*	7. COMPUTED BY *(Signature)*	8. CHECKED BY *(Signature)*

CBR FAMILY OF CURVES

W *(Percent)*		BLOWS/LAYER	BLOWS/LAYER	BLOWS/LAYER
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			
	DRY DENSITY, in pcf			
	CORRECTED CBR, in percent			

CBR FAMILY OF CURVES

CORRECTED CBR PERCENT



MOLDED DRY DENSITY, in pcf

DESIGN CBR

COMPACTION RANGE

_____ % TO _____ %

_____ LBS/FT^3 TO _____ LBS/FT^3

W *(Percent)*	LOWEST CBR	W PERCENT RANGE	ASSURED CBR
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		% TO %	
		DESIGN CBR (HIGHEST ASSURED) _____	
		DESIGN MOISTURE RANGE _____ % TO _____ %	

CBR SWELL DATA



NOTE: Maximum acceptable swell is 3 percent.